

VARIABLES FILE

The Variables File is where you set global styles throughout the website you are building. The variables within each section will control styling that uses these variables across multiple SCSS files.

Table of Contents

Colors-----	02
Typography-----	03
Body Font-----	04
Heading Font-----	05
Hyperlinks-----	06
Buttons-----	07
Global-----	09
Header-----	10
Nav Wrap-----	11
Top Nav Text-----	11
Reservation Button-----	12
Prime Nav-----	13
Dropdown Menu-----	14
Mobile Menu Button-----	15
Hero-----	15
Touts-----	16
Rooms-----	17
Specials-----	18
Blog-----	19
Footer-----	20
Sidebar-----	22
Vacation Guide-----	23
Featured Properties-----	24
Q4VR Styles-----	25

COLORS SECTION

```
// -----  
// *COLORS*  
// -----  
$color-white           : #ffffff;  
$color-black          : #000000;  
$trans                 : transparent;  
/* Custom Colors */  
$color-waikawa-gray    : #57608c;  
$color-dove-gray       : #6b6b6b;  
$color-blackcurrant   : #362c37;  
$color-thunder         : #3d393d;  
$color-buccaneer       : #743232;  
$color-dusty-gray      : #9b9b9b;  
$color-mine-shaft      : #3b3b3b;  
$color-alto            : #d4d4d4;  
$color-ebb             : #f1edec;  
$color-bali-hai        : #9298b4;  
$color-gallery         : #f0f0f0;
```

The color section is used to store variables for the different colors for our individual customer websites. The first three of this section (\$color-white, \$color-white, and \$trans) are the global colors used by every website we develop...DO NOT DELETE. The **Custom Colors** section are where you add website specific colors.

TYPOGRAPHY SECTION

```
// =====  
// *TYPOGRAPHY*  
// =====  
$font_import_url : GOOGLE FONTS;  
/*  
font-family: raleway, sans-serif;  
font-family: alegreya, serif;  
font-family: poppins, sans-serif;  
*/
```

The Typography section is where we set the font families related to our client's website. There is only one setting, adding the CDN link for Google Fonts. There are two platforms we use to import fonts, Google Fonts and Typekit. This setting is only used when importing fonts from **Google Fonts**, otherwise replace placeholder text with empty quotations (“”). If importing fonts from Typekit, paste the **Project ID** into the customizer setting (*learn more here*).

BODY FONT

```
// *BODY FONT*  
// -----  
$body_font           : poppins, sans-serif;  
$body_font_color    : $color-blackcurrent;  
$body_font_size     : 16;  
$font_scale         : 1.2;  
$line_height        : 1.5;
```

This is where you set the global styles for all body fonts throughout the website.

- **\$body_font**: Sets the font family for the body paragraph text
- **\$body_font_color**: Sets the font color for the body text
- **\$body_font_size**: Sets the font size for the body text. Use only a pixel value, the pixel value will auto calculate to a responsive value (ie rem, em, %, etc).
- **\$font_scale**: Measures the root document font setting (set with \$body_font variable) and converts it to a responsive value.
- **\$line_height**: Sets the line height for the body text

HEADING FONT

```
// *HEADING FONT*  
// -----  
$heading_font           : alegreya, serif;  
$heading_color          : $color-blackcurrant;  
$heading_weight         : 400;  
$heading_transform      : capitalize;  
$heading_style          : normal;  
$h5_size                : ($body_font_size * $font_scale);  
$h4_size                : ($h5_size * $font_scale);  
$h3_size                : ($h4_size * $font_scale);  
$h2_size                : ($h3_size * $font_scale);  
$h1_size                : ($h2_size * $font_scale);
```

This is where you set the global styles for all heading fonts throughout the website.

- **\$heading_font**: Sets the font family for all header text
- **\$heading_color**: Sets the font color for all header text
- **\$heading_weight**: Sets the font-weight for all header text
- **\$heading_transform**: Sets the font-transform styling for all header text
- **\$heading_styling**: Sets the font-style styling for all header text
- **\$h5_size - \$h1_size**: Sets the responsive font sizes for each header element (ie <h1> - <h6>)

HYPERLINKS

```
// *HYPERLINKS*  
// -----  
$link_color           : $color-blackcurrent;  
$link_hover_color    : $color-buccaneer;
```

This is where you set the global styles for all hyperlinks throughout the website.

- **\$link_color**: Sets the font color for all hyperlinks
- **\$link_hover_color**: Sets the font color on hover for all hyperlinks

BUTTONS

```
// *BUTTONS*  
// -----  
$button_font           : $body_font;  
$button_font_size     : 15px;  
$button_font_weight   : 700;  
$button_padding       : 8px 20px;  
$button_border_radius : 0;  
$button_font_transform : uppercase;  
$button_font_color    : $color-white;  
$button_background    : $color-waikawa-gray;  
$button_border        : none;  
$button_font_color_hover : $color-white;  
$button_background_hover : $color-buccaneer;  
$button_border_hover  : $button_border;
```

This is where you set the global styles for all buttons throughout the website.

- **\$button_font:** Sets the font-family for all buttons. The default setting uses the font-family from the `$body_font`.
- **\$button_font_size:** Sets the font-size for all buttons. The default setting uses the font-size setting from `$body_font_size`, if you are using a custom size be sure to use pixel values.
- **\$button_weight:** Sets the font-weight for all buttons.
- **\$button_padding:** Sets the padding for the anchor `<a>` elements on the button. Be sure to set pixel values
- **\$button_border_radius:** Sets the border radius for all buttons
- **\$button_font_transform:** Sets the font-transform styling for all buttons
- **\$button_font_color:** Sets the font color of all button fonts. Controls the anchor element
- **\$button_background:** Sets the background-color for all buttons. Controls the anchor element
- **\$button_border:** Sets the border styling for all buttons
- **\$button_font_color_hover:** Sets the font color on hover

- **\$button_background_hover:** Sets the background-color on hover. Controls anchor element
- **\$button_border_hover:** Sets the border-color on hover.

GLOBAL

```
// -----  
// *GLOBAL*  
// -----  
$endless_footer_color           : $color-thunder;  
$homepage_background            : $color-white;  
$internal_background            : $homepage_background;  
$section_header_font           : $heading_font;  
$section_header_font_size      : $h2_size;  
$section_header_transform      : capitalize;  
$section_header_padding        : 0;  
$section_bottom_padding        : 0;  
$section_button_padding        : 20px 0 0 0;
```

This is where you set the global styles for all buttons throughout the website.

- **\$endless_footer_color:** Sets the footer color for all footer sections. You have the option to set individual colors for individual sections in the footer section.
- **\$homepage_background:** Sets the background-color of the homepage body
- **\$internal_background:** Sets the background-color for the internal pages
- **\$section_header_font:** Sets the custom font-family for all section headers (ie Blog Section, Specials Section, Accommodations Sections, etc). The default setting is \$header_font.
- **\$section_header_font_size:** Sets the custom font-size for all section headers. The default setting is \$h2_size.
- **\$section_header_transform:** Sets the custom font-transform for all section headers. The default value is capitalize
- **\$section_header_padding:** Sets the padding for all section headers
- **\$section_bottom_padding:** Sets the padding-bottom styling for each section
- **\$section_button_padding:** Sets the margin-top and/or margin-bottom for all buttons.

HEADER

```
// =====  
// *HEADER*  
// =====  
// NAV WRAP  
$nav_wrap_background_color      : $color-white;  
  
// TOP NAV TEXT  
$top_nav_text_font              : $body_font;  
$top_nav_text_color             : $color-dove-gray;  
$top_nav_text_hover_color      : $color-buccaneer;  
$top_nav_text_size              : $body_font_size;  
$top_nav_text_weight            : 600;  
  
// RESERVATION BUTTON  
$reservation_background         : $button_background;  
$reservation_border             : $button_border;  
$reservation_padding           : $button_padding;  
$reservation_font_color        : $button_font_color;  
$reservation_background_hover  : $button_background_hover;  
$reservation_border_hover      : $button_border_hover;  
$reservation_font_color_hover  : $button_font_color_hover;  
$reservation_font_size         : $button_font_size;  
$reservation_font_weight       : $button_font_weight;  
$reservation_border_radius     : $button_border_radius;  
$reservation_font_transform    : $button_font_transform;  
  
// PRIME NAV  
$prime_nav_background          : $color-gallery;  
$prime_nav_background_hover    : $trans;  
$prime_nav_font_color          : $color-dove-gray;  
$prime_nav_font_color_hover    : $color-buccaneer;  
$prime_nav_font                : $body_font;  
$prime_nav_font_size           : $body_font_size;  
$prime_nav_font_weight         : 600;  
$prime_nav_transform           : capitalize;  
$prime_nav_padding             : 20px 15px;  
  
// DROPDOWN MENU  
$dropdown_background           : $color-thunder;  
$dropdown_background_hover     : $color-buccaneer;  
$dropdown_font_size            : $prime_nav_font_size;  
$dropdown_font_color           : $color-white;  
$dropdown_font_color_hover     : $color-white;  
$dropdown_padding              : 15px 24px;  
  
// MOBILE MENU BUTTON  
$mobile_menu_background        : transparent;  
$mobile_menu_background_hover  : transparent;  
$mobile_menu_font_color        : $heading_color;
```

This is where you set the global styles for the header styles.

Nav Wrap

```
// NAV WRAP
$nav_wrap_background_color : $color-white;
```

- **\$nav_wrap_background_color:** Sets the background-color for the nav-wrap header

Top Nav Text

```
// TOP NAV TEXT
$top_nav_text_font           : $body_font;
$top_nav_text_color         : $color-dove-gray;
$top_nav_text_hover_color   : $color-buccaneer;
$top_nav_text_size          : $body_font_size;
$top_nav_text_weight        : 600;
```

Inline with logo and above the prime navigation menu

- **\$top_nav_text_font:** Sets the font-family for top nav text
- **\$top_nav_text_color:** Sets the font color for top nav text
- **\$top_nav_text_hover:** Sets the font color on hover for top nav text
- **\$top_nav_text_size:** Sets the font-size for top nav text
- **\$top_nav_text_weight:** Sets the font-weight for top nav text

Reservation Button

```
// RESERVATION BUTTON
$reservation_background      : $button_background;
$reservation_border         : $button_border;
$reservation_padding        : $button_padding;
$reservation_font_color     : $button_font_color;
$reservation_background_hover : $button_background_hover;
$reservation_border_hover   : $button_border_hover;
$reservation_font_color_hover : $button_font_color_hover;
$reservation_font_size      : $button_font_size;
$reservation_font_weight    : $button_font_weight;
$reservation_border_radius  : $button_border_radius;
$reservation_font_transform : $button_font_transform;
```

This is where you set the Reservation Button styles in the header

NOTE: Keep the default values as is, rarely will these ever need to be changed.

- **\$reservation_background:** Sets the background-color for the reservation button. Default setting is \$button_background.
- **\$reservation_border:** Sets the border styling
- **\$reservation_padding:** Sets the padding and margin styling
- **\$reservation_font_color:** Sets the font color for the reservation button anchor element
- **\$reservation_background_hover:** Sets the hover styling for the reservation anchor tag
- **\$reservation_border_hover:** Sets the hover styling for the reservation anchor tag border
- **\$reservation_font_color_hover:** Sets the hover color for the reservation anchor tag
- **\$reservation_font_size:** Sets the font-size for the reservation button
- **\$reservation_font_weight:** Sets the font-weight for the reservation anchor tag
- **\$reservation_border_radius:** Sets the border-radius for the anchor tag
- **\$reservation_font_transform:** Sets the text-transform for the reservation anchor tag

Prime Nav

```
// PRIME NAV
$prime_nav_background      : $color-gallery;
$prime_nav_background_hover : $trans;
$prime_nav_font_color      : $color-dove-gray;
$prime_nav_font_color_hover : $color-buccaneer;
$prime_nav_font             : $body_font;
$prime_nav_font_size       : $body_font_size;
$prime_nav_font_weight     : 600;
$prime_nav_transform       : capitalize;
$prime_nav_padding         : 20px 15px;
```

This is where you set the Primary Navigation (nav menu) styles in the header

- **\$prime_nav_background:** Sets the background-color of the primary navigation area.
- **\$prime_nav_background_hover:** Sets the background-color for the primary navigation hover state.
- **\$prime_nav_font_color:** Sets the color for the primary navigation fonts.
- **\$prim_nav_font_color_hover:** Sets the hover state color for the primary navigation.
- **\$prime_nav_font:** Sets the font-family of the primary navigation fonts.
- **\$prime_nav_font_size:** Sets the font-size for the primary navigation fonts.
- **\$prime_nav_font_weight:** Sets the font-weight for the primary navigation fonts.
- **\$prime_nav_transform:** Sets the text-transform for the primary navigation fonts.
- **\$prime_nav_padding:** Sets the padding for the primary navigation links.

Dropdown Menu

```
//DROPDOWN MENU
$dropdown_background           : $color-thunder;
$dropdown_background_hover    : $color-buccaneer;
$dropdown_font_size           : $prime_nav_font_size;
$dropdown_font_color          : $color-white;
$dropdown_font_color_hover    : $color-white;
$dropdown_padding             : 15px 24px;
```

This is where you set the Dropdown menu items for the Primary Navigation (nav menu) styles in the header

- **\$dropdown_background:** Sets the background-color of the dropdown menu.
- **\$dropdown_background_hover:** Sets the background-color for the dropdown hover state
- **\$dropdown_font_size:** Sets the font-size for the dropdown menu fonts.
- **\$dropdown_font_color:** Sets the color for the dropdown menu fonts.
- **\$dropdown_font_color_hover:** Sets the color for the hover state of the dropdown fonts.
- **\$dropdown_padding:** Sets the padding for the dropdown menu items.

Mobile Menu Button

```
// MOBILE MENU BUTTON
$mobile_menu_background      : transparent;
$mobile_menu_background_hover : transparent;
$mobile_menu_font_color      : $heading_color;
```

This is where you set the Hamburger Menu icon styles

*NOTE: Keep the default values as is, rarely will these ever need to be changed. These variables control the styling for the Hamburger icon only, this **does not** control mobile view of the dropdown menus.*

- **\$mobile_menu_background**: Sets hamburger menu background-color
- **\$mobile_menu_background_hover**: Sets hamburger menu background-color on hover
- **\$mobile_menu_font_color**: Sets hamburger menu bar icons color

HERO

```
// *HERO*
// -----
$carousel_background_color : $trans;
```

This where you will set the Carousel (hero) styles.

Note: Unless otherwise designed, we keep the default setting of \$trans.

- **\$carousel_background_color**: Sets the background-color of the carousel (hero) area.

TOUTS

```
// *TOUTS*
// -----
$tout_background           : $trans;
$tout_background_hover    : $trans;
$tout_font                 : $heading_font;
$tout_font_color          : $heading_color;
$tout_position             : 0;
$tout_height               : 100%;
$tout_position_hover      : 0;
$tout_height_hover        : 100%;
$tout_width                : 1800px;
$tout_side_padding        : 10px;
$tout_top_padding         : 15px;
```

This where you will set the Tout styling for the global tout designs.

NOTE: Some of these variables may become irrelevant if using the gradient overlay instead of the standard block overlay on the touts. If using the gradient overlay be sure to set the `$tout_background` and `$tout_background_hover` values to `$trans`, otherwise there will be two background color values competing and can cause conflict.

- **`$tout_background`**: Sets the background-color of the tout overlay.
- **`$tout_background_hover`**: Sets the background-color of the tout overlay hover state.
- **`$tout_font`**: Sets the font-family for the tout text.
- **`$tout_font_color`**: Sets the font color for the tout text.
- **`$tout_postion`**: Sets the position alignment for the tout caption (will need to provide a percentage value).
- **`$tout_height`**: Sets the height (percentage) value of the tout caption (text and overlay).
- **`$tout_position_hover`**: Sets the position alignment for the tout caption (will need to provide a percentage value) on hover state.
- **`$tout_height_hover`**: Sets the height (percentage) value of the tout caption (text and overlay) on hover state.

- **\$tout_width**: Sets the max-width for the tout parent container.
- **\$tout_side_padding**: Sets the left and right padding values for the individual touts.
- **\$tout_top_padding**: Sets the padding-top value for the tout parent container.

ROOMS

```
// *ROOMS*
// -----
$rooms_section_heading_color      : $heading_color;
$rooms_background                 : rgba($color-ebb, 0.75);
$rooms_panel_background           : $color-thunder;
$rooms_panel_padding              : 0;
$rooms_heading_color              : $color-white;
$rooms_heading_weight             : 400;
$rooms_heading_size               : $body_font_size;
$rooms_text_color                 : $color-white;
```

This where you will set the Rooms/Accommodations styling.

NOTE: Depending on the design of this section, some variables may be irrelevant.

- **\$rooms_section_heading_color**: Sets the Rooms/Acc section heading font color.
- **\$rooms_background**: Sets the Rooms/Acc section background-color.
- **\$rooms_panel_background**: Sets the Rooms/Acc panel overlay background-color...this is only relevant to design options 2 and 3.
- **\$rooms_panel_padding**: Leave this section as the default. This is better controlled in the styling code found in the code library...only relevant to design option 2 and 3.
- **\$rooms_heading_color**: Sets the heading font color for the room/acc excerpt block.
- **\$rooms_heading_weight**: Sets the font-weight for the heading font in the excerpt block.
- **\$rooms_heading_size**: Sets the font-size for the heading font in the excerpt block.
- **\$rooms_text_color**: Sets the font color for the text in the excerpt block.

SPECIALS

```
// *SPECIALS*  
// -----  
$specials_section_heading_color : $color-white;  
$specials_background           : $color-buccaneer;  
$specials_overlay_background   : $trans;  
$specials_text_color           : $color-white;  
$specials_text_font            : $heading_font;  
$specials_text_weight          : 400;  
$specials_text_size            : $body_font_size;  
$specials_overlay_hover       : $trans;
```

This where you will set the Global styling for the Specials section.

NOTE: Depending on the design of this section, some variables may be irrelevant.

- **\$specials_section_heading_color:** Sets the section heading font color.
- **\$specials_background:** Sets the section background-color.
- **\$specials_overlay_background:** Sets the overlay background-color for the individual specials...very rarely will there be a design that has the overlay option, sets this section value to \$trans.
- **\$specials_text_color:** Sets the font color for the Special Titles (not section title)...NOTE: The color does not always pull through (anchor tag color is competing) and will need to be updated in the specials styling code from the code library (look for the commented code).
- **\$specials_text_font:** Sets the specials title font-family.
- **\$specials_text_weight:** Sets the specials title font-weight.
- **\$specials_text_size:** Sets the specials title font-size.
- **\$specials_overlay_hover:** Sets the overlay background-color hover state for the individual specials...very rarely will there be a design that has the overlay option, sets this section value to \$trans.

BLOG

```
// *BLOG*  
// -----  
$blog_section_heading_color      : $heading_color;  
$blog_background                 : $trans;  
$blog_heading_color              : $color-white;  
$blog_heading_font               : $body_font;  
$blog_heading_weight             : 400;  
$blog_heading_size               : $body_font_size;  
$blog_text_color                 : $body_font_color;  
$blog_overlay_background         : rgba($color-mine-shaft, 0.8);  
$blog_overlay_background_hover   : $color-thunder;
```

This is where you will set the Global styling for the Blog section.

NOTE: Depending on the design of this section, some variables may be irrelevant.

- **\$blog_section_heading_color:** Sets the blog section title font color.
- **\$blog_background:** Sets the blog section background-color.
- **\$blog_heading_color:** Sets the blog title font title.
- **\$blog_heading_font:** Sets the blog title font-family.
- **\$blog_heading_weight:** Sets the blog title font-weight.
- **\$blog_heading_size:** Sets the blog title font-size.
- **\$blog_text_color:** Sets the blog title font color.
- **\$blog_overlay_background:** Sets the blog overlay background-color...NOTE: if using the gradient overlay design set this value to \$trans. The gradient overlay code is in the blog styling code located in the code library.
- **\$blog_overlay_background_hover:** Sets the blog overlay background-color on hover state...NOTE: if using the gradient overlay design, set this value to \$trans. The gradient overlay code is in the blog styling code located in the code library.

FOOTER

```
// *FOOTER*  
// -----  
$first_footer_background      : $endless_footer_color;  
$second_footer_background    : $color-white;  
$last_footer_background      : $endless_footer_color;  
$footer_heading_color        : $color-white;  
$footer_font_color           : $color-white;  
$footer_link_hover_color     : $color-bali-hai;  
$footer_top_padding          : 118px;  
$footer_bottom_padding       : 46px;  
$footer_heading_padding      : 14px;  
$social_icon_padding         : 10px;  
$social_icon_color           : $color-white;  
$social_icon_hover_color     : $link_hover_color;
```

This is where you will set the Global styling for the Footer section.

NOTE: This section has been updated and will require using the PHP/HTML, SCSS, and additional variables located in the code library for these settings to work.

- **\$first_footer_background:** Sets the blog title font color.
- **\$second_footer_background:** Sets the blog title font color.
- **\$last_footer_background:** Sets the blog title font color.
- **\$footer_heading_color:** Sets the blog title font color.
- **\$footer_font_color:** Sets the blog title font color.
- **\$footer_link_hover_color:** Sets the blog title font color.
- **\$footer_top_padding:** Sets the blog title font color.
- **\$footer_bottom_padding:** Sets the blog title font color.
- **\$footer_heading_padding:** Sets the blog title font color.
- **\$social_icon_padding:** Sets the blog title font color.
- **\$social_icon_color:** Sets the blog title font color.
- **\$social_icon_hover_color:** Sets the blog title font color.

Added Variables (located in the styling code library file)

- **\$footer_heading_transform:** Sets the footer titles font-transform.
- **\$footer_heading_size:** Sets the footer titles font-size.
- **\$footer_weather_temp_font:** Sets the footer Awesome Weather Widget temperature font-family.
- **\$footer_weather_temp_weight:** Sets the footer Awesome Weather Widget temperature font-weight.
- **\$credit_padding:** Sets the credits (last footer row) padding.
- **\$credit_size:** Sets the credits (last footer row) font-size.
- **\$credit_transform:** Sets the credits (last footer row) font-transform.
- **\$credit_weight:** Sets the credits (last footer row) font-weight.
- **\$footer_width:** Sets the footer parent container max-width (use pixel value).

SIDEBAR

```
// *SIDEBAR*  
// -----  
$sidebar_background      : $tout_background;  
$sidebar_background_hover : $tout_background_hover;  
$sidebar_color           : $tout_font_color;  
$sidebar_position        : $tout_position;  
$sidebar_height          : $tout_height;  
$sidebar_position_hover  : $tout_position_hover;  
$sidebar_height_hover    : $tout_height_hover;
```

This is where you will set the Global styling for the Sidebar Touts.

NOTE: Leave the default values as is, rarely will you need to change these.

- **\$sidebar_background:** Sets the background-color of the sidebar tout overlay.
- **\$sidebar_background_hover:** Sets the background-color of the sidebar tout overlay hover state.
- **\$sidebar_color:** Sets sidebar tout font color.
- **\$sidebar_position:** Sets sidebar tout position.
- **\$sidebar_height:** Sets sidebar tout height.
- **\$sidebar_position_hover:** Sets sidebar tout position hover state.
- **\$sidebar_height_hover:** Sets sidebar tout height hover state.

VACATION GUIDE

```
// *VACATION GUIDE*  
/* -----*/  
$og_nav_color           : $prime_nav_background;  
$og_primary_color      : $color-black;  
$og_secondary_color    : $color-white;  
$og_title_background   : $og_primary_color;  
$og_title_color        : $color-white;  
$section_color         : $color-white;  
$section_background_color : rgba($og_primary_color, 0.5);  
$section_accent        : rgba($og_primary_color, 0.75);  
$section_blurb_background : $og_primary_color;  
$section_blurb_color   : $color-white;  
$line-item-divider     : rgba($og_primary_color, 0.25);  
$sub-section-color     : $og_primary_color;  
$sub_section_accent    : $og_secondary_color;  
$rating-color          : gold;
```

This is where you will set the Global styling for the Vacation Guide.

*NOTE: These variables only become relevant when the Q4OG plugin is activated. Most of these variables can be left as their default values. The only variables that are required to set are the **\$of_primary_color** and **\$og_secondary_color**.*

FEATURED PROPERTIES

```
// *FEATURED PROPERTIES*  
// -----  
$featured_vr_background      : $color-white;  
$featured_vr_width           : 1500px;  
$featured_vr_card_padding    : 0;  
$featured_vr_card_background : $color-white;  
$featuerd_vr_text_padding    : 0 0;  
$featured_vr_heading_size    : 1rem;  
$featured_vr_heading_color   : $color-black;  
$featured_vr_heading_padding : 30px;  
$featured_vr_stat_size       : 18px;  
$featured_vr_stat_color      : $color-black;  
$featured_vr_button_color    : $color-white;  
$featured_vr_button_background : $color-black;  
$featured_vr_button_color_hover : $color-black;  
$featured_vr_button_background_hover : $color-white;  
$featured_vr_button_padding  : 0 0;  
$featured_vr_button_size     : 1rem;
```

This section is no longer relevant and can be ignored. We have a shortcode that sets up this section and now uses different styling and variables. This section will be updated in the new framework (Q4FW-3).

Q4VR STYLES

```
// *Q4VR STYLES*  
// -----  
$search_bar_background      : $prime_nav_background;  
$search_bar_height         : auto;  
$date_selector_primary_background : $color-black;  
$date_selector_primary_color  : $color-white;  
$date_selector_secondary_background : $color-white;  
$date_selector_secondary_color  : $color-black;
```

This section is no longer relevant and can be ignored. We have built a new VR plugin that uses different variables and styling. This section will be updated in the new framework (Q4FW-3).